


NEW!

CRACKLE SPIRIT

2-STEP-CRACKLE-SYSTEM FOR VERY FINE STRUCTURES

For picture frames, furniture, interior doors, etc.



Step 1: 0L5
Step 2: 0L5

- Crackle varnish for simulating cracked paintwork. Decorative technology as part of the trends in antique trimmed surfaces.
- Water-based.
- Fast drying.
- Creates numerous, very fine cracks.
- For horizontal and vertical surfaces indoors.

Crackle Spirit is a system for producing a decorative cracked surface. Produces very fine crack structures ("porcelain crack"). This system consists of two transparent successively applied products (STEP 1 and STEP 2).

2 APPLICATION METHODS ARE POSSIBLE:

Method 1

CRACKLE SPIRIT STEP 1 and STEP 2 are used in the transparent form as delivered. Thus, the original base remains visible and technically fully intact. Crackles created in the transparent coat are coloured afterwards.

Method 2

CRACKLE SPIRIT STEP 1 and STEP 2 are tinted in different colors. The result is a surface in the shade of STEP 2 with cracks in the shade of STEP 1.

METHODE 1:

Do not tint STEP 1 and STEP 2! After 1 to 2 hours, the resultant cracks may be colored by rubbing in colored dispersion, colored hard wax or tinting pastes.

The rubbing is done with a clean cloth, excess paint / wax must be wiped away carefully. So the impression is like cracks in the original surface.



Paint

Crackle Spirit STEP 1

Crackle Spirit STEP 2



Wipe off

Result

METHODE 2:

Tint STEP 1 and STEP 2 in custom colours! So with only two steps there is a result of cracked surface with STEP-1-coloured crackles in a STEP-2-coloured background.



Crackle Spirit STEP 1

Crackle Spirit STEP 2

Result